

Cordless circular saw with pendulum hood 18,0 V

CS 62 18.0-EC C

Order number 491.322



Cordless circular saw with pendulum hood 18,0 V

- + Electronic management system (EMS) protects the machine, extends the service life, and increases efficiency
- + Brushless motor with greater efficiency and a longer service life
- + 18.0 V EC motor with overload protection and temperature monitoring
- + LED battery capacity display
- + Dual clamped swivel element prevents the saw blade from jamming when making mitre cuts and therefore the risk of recoil
- + Spindle lock: for quick replacement of blades
- + Angle scale from 0° to 50°. With preset angles of 22.5° / 45°, and 50°. Easy to read, precision adjustment via non-slip clamping elements
- + Swivel range from 0° to 50° for undercuts as well as scoring function for perfect visible edges
- + Intuitive clamp lever for cutting depth adjustment, cutting depth is easy to read off
- + In accordance with the latest regulations without splitting wedge for plunge cuts and without time-consuming removal of splitting wedge
- + Woodshaving collection bag for low-dust operation, simple to empty, tool-free attachment by means of bayonet connection
- + Connector for external dust extraction Ø 27 mm or step adapter
- + Ideal for traditional applications in dry construction and refurbishing, e.g. for making saw cuts through plasterboard, concrete fibre boards, wood materials, such as chipboard or OSB boards
- + FLEX battery system: suitable for all 18,0 V battery packs. Delivery does not include battery and charger

Technical attributes

Battery voltage	18 V
Battery capacity	2,5 / 5,0 Ah
No load speed	5000 rpm
Pivoting range	0-50 °
Saw blade holder	20 mm
Cutting depth	0-62 mm
Depth of cut - mitre cut	0-38 mm
Depth of cut - mitre cut with guide rail	0-32 mm
Blade Ø	165 mm
Angle preset	0°/22,5°/45°/50°
Size (W x L x H)	380 x 150 x 200 mm
Weight without battery	3,1 kg

Standard equipment

1 saw blade Z 24-WZ	456.012
1 dust bag	1 piece
1 extraction adapter	1 piece

FLEX-Elektrowerkzeuge GmbH
Bahnhofstraße 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX
Das Original

Accessories

Standard circular saw blade with alternating teeth

Order number 456.012



Technical attributes	
Dimensions in mm	165 Ø x 20
QTY/PKG	1

For making long cuts and for sawing wood materials, such as chipboard, OSB, MDF boards.

Carrying case L-BOXX®

Order number 414.107



Technical attributes	
External dimensions L x W x H	442 x 357 x 389 mm
Internal dimensions L x W x H	378 x 296 x 345 mm
Weight	3,4 kg
QTY/PKG	1

The robust storage and transport system L-BOXX® made of impact-resistant plastic conveys tools, accessories and consumables easily and comfortably to the place of use. Elaborate inserts provide order and clarity, ergonomically shaped handles and additional moulded recesses for flexible and comfortable handling. The unbeatably simple connection and disconnection of the different L-BOXXes optimises combined transportation. Fits the TÜV-tested in-vehicle equipment system from Sortimo perfectly and without adapters. Load capacity per L-BOXX® up to 25 kg, combined transportation up to 40 kg, the cover can be loaded up to 100 kg. Splash-proof. Without insert.

FLEX-Elektrowerkzeuge GmbH
Bahnhofstraße 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX
Das Original

Accessories

Adapter for guide rail

Order number 467.065



Technical attributes

QTY/PKG	1
---------	---

Can be mounted tool-free. Perfect guidance of the CS 62 on the FLEX guide rail for cuts of 0-50° (Festool guide rail 0°).

Guide rail GRS

Order number 353.280



Technical attributes

Length in mm	800
QTY/PKG	1

Precise aluminium profile with anodized sliding coating and guide rib. Plugged rubber lip as contact edge at the marking, anti slip protection on the bottom. Connector 353.272 can be used to extend the guide rails as required.

FLEX-Elektrowerkzeuge GmbH
Bahnhofstraße 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX
Das Original

Accessories

Guide rail GRS

Order number 359.351



Technical attributes

Length in mm	1600
QTY/PKG	1

Precise aluminium profile with anodized sliding coating and guide rib. Plugged rubber lip as contact edge at the marking, anti slip protection on the bottom. Connector 353.272 can be used to extend the guide rails as required.

Connector for guide rail GRS

Order number 353.272



Technical attributes

QTY/PKG	1
---------	---

Precise metal connector for connecting two guide rails GRS. When not in use, the connector can be parked in the guide rail with the included tool wrench SW 5 - screw driver.

FLEX-Elektrowerkzeuge GmbH
Bahnhofstraße 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX
Das Original

Accessories

Battery powered heating jacket



Heated, high-quality soft shell jacket with comfortable fleece lining, various pockets, and detachable hood. Wind and water repellent material for high durability. Three heating zones for individual heating settings and quick heat function. 10,5/21 hours of heat at level 1, 9,5/19 hours at level 2, and 5/10 hours at level 3 (2,5/5,0 Ah 18,0 V). Suitable for 10,8 and 18,0 V lithium ion battery. Battery adapter with USB port for charging smartphones. Battery not included.

Technical attributes

Size	QTY/PKG	Order number
M	1	417.998
L	1	423.165
XL	1	423.173
XXL	1	423.181

LED worklamp

Order number 417.955



Technical attributes

QTY/PKG	1
---------	---

Powerful LED worklamp with 24 cold-white LEDs and integrated discharge protection. LED head can be swivelled through 320° and folded through 180°. Swivelling and lowerable hook for attaching the lamp and belt clip. Lighting duration: approx 20 hours with 2.5 Ah battery pack and approx 40 hours with 5.0 Ah battery pack. FLEX battery system: suitable for all 18 V battery packs. Delivery does not include battery.

FLEX-Elektrowerkzeuge GmbH
Bahnhofstraße 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX
Das Original

Accessories

Carrying bag

Order number 491.365



Technical attributes

Size (W x L x H)	510 x 165 x 280 mm
QTY/PKG	1

Practical carrying bag made from plastic-reinforced, tear-resistant textile material with a very wide opening. With large storage space for up to three tools as well as compartments for accessories such as batteries, charger etc. and five exterior pockets on the front. Fitted with rubber feet, lockable zip fastener, cushioned carrying strap and steel-reinforced handles.