

FLEX-Elektrowerkzeuge GmbH
Bahnhofstraße 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX
Das Original

Diamond cutting system, 230 mm

DCG L 26-6 230 G-Set

Order number 494.674



Diamond cutting system, 230 mm

- + Ready to go straight away, angle grinder with already installed extraction hood in the case. Diamantjet - Standard 230 mm diamond cutting wheel for concrete included
- + Powerful angle grinder L 26-6 230 with soft start, restart protection after power failure, overload protection, CDC-electronic feedback control, anti-kickback function
- + Fully encapsulated extraction hood for efficient dust extraction
- + Direct connection via Flex Clip system
- + Extremely sturdy construction. The stabiliser element prevents distortion caused by the side weight of the angle grinder.
- + Base plate with rollers for easy feed. Can be used with or without a guide rail
- + Depth stop with scale for cutting depth adjustments and individual cuts (plunge cuts) with or without guide rail (max. 55 mm with, 60 mm without guide rail)
- + Side handle can be fitted on either the left or right
- + Case including lid compartment for small parts, storage space for diamond cutting wheel, side handle and 800 mm guide rail.

Technical attributes

Max. disc diameter	230 mm
No load speed	6500 rpm
Power input	2600 watt
Power output	1800 watt
Tool fixture	M 14
Cutting depth / with guide rail	60 / 55 mm
Clamping collar Ø	64 mm
Cable length	4,0 m
Size (L x W x H, including extraction hood)	610 x 195 x 290 mm
Weight with dust extraction guard	9,18 kg

Standard equipment

1 dust extraction guard DCG AG 230	471.895
1 diamond cutting disc, universal	500.720
1 guide rail GRS 80	353.280
1 DCG AG set rubber strips (3 pcs)	494.593
1 DCG AG 230 distance ring L26/24/22	494.615
1 SoftVib handle	325.384
1 clamping flange	338.753
1 clamping nut M14	100.080
1 hexagon socket wrench, SW 6	104.167
1 pin wrench	100.110
1 carrying case with insert	499.579

FLEX-Elektrowerkzeuge GmbH
Bahnhofstraße 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX
Das Original

Accessories

Carrying case

Order number 499.579



Impact-resistant plastic case for the diamond cutting system DCG L 26-6 230 set. Including insert for suction hood, 230 mm angle grinder, compartment for 800 mm guide rail and small parts.

Technical attributes

External dimensions L x W x H	610 x 195 x 290 mm
QTY/PKG	1

Dust extraction guard cutting for large angle grinder, 230 mm

Order number 471.895



Detachable extraction hood with efficient dust extraction for precise cuts when working with diamond cutting wheels in conjunction with 230 mm angle grinders. Extremely stable, the stabiliser element prevents distortion caused by the side weight of the angle grinder. Base plate with rollers for easy feed, the side handle can be fitted on either the left or right. Incl. suction connection for FLEX clip system and adapter for guide rail. Depth stop with scale for presetting the cutting depth for use with or without a guide rail. Maximum cutting depth 60 mm.

Technical attributes

Diameter in mm	230
Size (W x L x H)	365x195x290 mm
QTY/PKG	1

FLEX-Elektrowerkzeuge GmbH
Bahnhofstraße 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX
Das Original

Accessories

Diamantjet - diamond cutting disc, universal

Order number 500.720



Technical attributes

Dimensions in mm	230 Ø 22,2
QTY/PKG	1

Universal cutting wheel for the most common construction site materials such as concrete B45 (hard concrete), soft granite, clinker and brick.

Diamantjet - diamond cutting disc, standard, concrete

Order number 349.054



Technical attributes

Dimensions in mm	230 Ø x 22,2
QTY/PKG	1

Fast, long-life universal cutting disc, suitable for concrete and stone