

4-speed cordless drill driver 18,0 V

DD 4G 18.0-EC C



4-speed cordless drill driver 18,0 V

+ Electronic management system (EMS) protects the machine, extends the service life, and increases efficiency

- + Brushless motor with greater efficiency and a longer service life
- + 4-speed gearbox of up to 4200 rpm for maximum drilling and screwdriving efficiency
- + Accelerator trigger with lock-off switch
- + Electronic quick-acting brake
- + Robust gearbox housing made of die-cast aluminium
- + Metal quick-clamp chuck with thrust ring and auto lock function
- + Drilling chuck can be removed without tools
- + Right/left rotation with safety catch
- + Extendable handle offers user protection even at maximum torque
- + Ergonomically designed, non-slip, soft grip handle
- + Integrated LED lamp with persistence function
- + LED battery capacity display
- + Including attachable auxiliary handle, belt clip and bit storage

+ FLEX battery system: suitable for all 18,0 V battery packs. Delivery does not include battery and charger

Order number 491.292

Technical attributes	
Battery voltage	18 V
Battery capacity	2,5 / 5,0 Ah
Max soft/hard torque	64 / 135 Nm
Torque positions	11+1
No load speed	460 / 910 / 2100 / 4200 rpm
Chuck Ø	1,5 - 13 mm
Max. drill hole Ø in steel	13 mm
Max. drill hole Ø in wood	76 mm
Weight without battery	1,5 kg

Standard equipment

1 handle	489.417
1 belt clip	467.154
1 bit holder	453.994
1 bit storage	430.862

Accessories

Keyless chuck



With rotation stop, for clamping shank tools Ø 1,5-13 mm.

Bit holder



For holding ¼" bits.

Angle attachment



FLEX Das Original

Order number 453.986

Technical attributes		
QTY/PKG	1	

Order number 453.994

Technical attributes		
QTY/PKG	1	

Order number 454.001

Technical attributes		
QTY/PKG	1	

Tool-free quick-change system when drilling and screwdriving in areas which are difficult to access. With magnetic drill spindle for holding drill



Order number 455.881

and screwdriver bits and for holding the keyless chuck and bit holder (only for DD/PD 18.0-EC).

Bit set



Technical attributesQTY/PKG1

Set consisting of 18 high-performance torsion bits: 2x T10, 2x T15, 2x T20, 2x T25, 2x T30, 2x T40, PH1, PH2, PH3, PZ1, PZ2, PZ3 and quick-lock bit holder.

Li-Ion rechargeable battery pack 18,0 V



Order number 445.886

Technical attributes	
Battery capacity	2,5 Ah
Battery voltage	18,0 V
Weight	0,42 kg
QTY/PKG	1

Battery pack Li ion 18.0 V with integrated charge and discharge protection, battery charge indicator, dust and splash protection. Electronic management system (EMS) protects the battery pack, extends the service life, and increases efficiency.



Accessories

Li-Ion rechargeable battery pack 18,0 V



Order number 445.894

Technical attributes	
Battery capacity	5,0 Ah
Battery voltage	18,0 V
Weight	0,72 kg
QTY/PKG	1

Battery pack Li ion 18.0 V with integrated charge and discharge protection, battery charge indicator, dust and splash protection. Electronic management system (EMS) protects the battery pack, extends the service life, and increases efficiency.

Rapid charger



Order number 417.882 Technical attributes

1

QTY/PKG

For charging 10.8 and 18.0 V battery packs. With large-format LCD display for battery diagnostics and charge levels. Charging time 10.8 V approx. 40 min. for 2.5 Ah / 4.0 Ah and approx. 55 min. for 6.0 Ah batteries. Charging time 18 V: approx 40 min for 2.5 Ah and approx 45 min for 5.0 Ah. A special procedure charges 80% of the capacity after about 30 min. With integrated battery pack cooler and overheating, discharge, and overload protection.

Accessories

Auxiliary handle



Order number 489.417

Technical attributes		
QTY/PKG	1	

The extra handle can be extended in three steps and reliably absorbs the occurring torque. Suitable for the cordless drill/screwdriver DD 4G 18.0-EC.

Carrying case L-BOXX®



Order number 414.085

Technical attributes	
External dimensions L x W x H	442 x 357 x 151 mm
Internal dimensions L x W x H	378 x 311 x 107 mm
Weight	2,2 kg
QTY/PKG	1

The robust storage and transport system L-BOXX[®] made of impact-resistant plastic conveys tools, accessories and consumables easily and comfortably to the place of use. Elaborate inserts provide order and clarity, ergonomically shaped handles and additional moulded recesses for flexible and comfortable handling. The unbeatably simple connection and disconnection of the different L-BOXXes optimises combined transportation. Fits the TÜV-tested in-vehicle equipment system from Sortimo perfectly and without adapters. Load capacity per L-BOXX[®] up to 25 kg, combined transportation up to 40 kg, the cover can be loaded up to 100 kg. Splash-proof. Without insert, with additional front handle.



Accessories

Carrying bag



FLEX Das Original

Order number 491.365

Technical attributes	
Size (W x L x H)	510 x 165 x 280 mm
QTY/PKG	1

Practical carrying bag made from plastic-reinforced, tear-resistant textile material with a very wide opening. With large storage space for up to three tools as well as compartments for accessories such as batteries, charger etc. and five exterior pockets on the front. Fitted with rubber feet, lockable zip fastener, cushioned carrying strap and steel-reinforced handles.

Power 55 R



Set consisting of a 10.8/18.0 V rapid charger and two 5.0 Ah 18.0 V battery packs.

Order number 491.349

Technical attributes		
QTY/PKG	1	

Accessories

Power 22 Q



Set consisting of a 18.0 V charger and two 2.5 Ah 18.0 V battery packs.



Order number 491.357

Technical attributes		
QTY/PKG	1	