

Cordless drywall screwdriver 18,0 V

DW 45 18.0-EC/2.5 Set

Order number 467.146



Cordless drywall screwdriver 18,0 V

- + Electronic management system (EMS) protects the machine, extends the service life, and increases efficiency
- + Brushless motor with greater efficiency and a longer service life
- + Accelerator trigger with lock-off switch
- + Electronic quick-acting brake
- + Right/left rotation with safety catch
- + Ergonomically designed, non-slip, soft grip handle
- + Integrated LED lamp with persistence function
- + LED battery capacity display
- + Ergonomically shaped soft handle with on/off switch and lock for continuous operation
- + Tool-free detachable depth stop
- + Including belt clip and bit storage
- + FLEX battery system: suitable for all 18,0 V battery packs

Technical attributes	
Battery voltage	18 V
Battery capacity	2,5 / 5,0 Ah
Max. torque	28 Nm
No load speed	0-4500 rpm
Tool fixture	1/4" hexagon socket
Max. screw diameter	4,2 mm
Weight without battery	0,975 kg

Ctddt	
Standard equipment	
1 bit holder UH-M 50 E6,3-C6,3	395.919
1 depth stop	1 piece
1 bit storage	430.862
1 belt clip	467.154
2 batteries 2.5 Ah AP 18.0/2.5	445.886
1 charger CA 10.8/18.0	417.882
1 carrying case L-BOXX [®] 136	414.085
1 case insert	466.840



Accessories

Screw magazine attachment



Order number 463.698

Technical attributes	
Weight	0,5 kg
QTY/PKG	1

For standard, belted screws. Screw magazine attachment rotates 360°, making it easy to reach into corners, tool-free screwing depth setting via wheel, tool-free adjustable depth stop to adapt to different screw lengths from 25-55 mm, max. shank diameter 4.2 mm. Ergonomic SoftGrip handles. Fits drywall screwdriver DW 45 18.0-EC.

Li-Ion rechargeable battery pack 18,0 V



Order number 445.886

Technical attributes	
Battery capacity	2,5 Ah
Battery voltage	18,0 V
Weight	0,42 kg
QTY/PKG	1

Battery pack Li ion 18.0 V with integrated charge and discharge protection, battery charge indicator, dust and splash protection. Electronic management system (EMS) protects the battery pack, extends the service life, and increases efficiency.



Accessories

Li-Ion rechargeable battery pack 18,0 V



Order number 445.894

Technical attributes	
Battery capacity	5,0 Ah
Battery voltage	18,0 V
Weight	0,72 kg
QTY/PKG	1

Battery pack Li ion 18.0 V with integrated charge and discharge protection, battery charge indicator, dust and splash protection. Electronic management system (EMS) protects the battery pack, extends the service life, and increases efficiency.

Rapid charger



Order number 417.882

Technical attributes		
QTY/PKG	1	

For charging 10.8 and 18.0 V battery packs. With large-format LCD display for battery diagnostics and charge levels. Charging time 10,8 V approx. 40 min. for 2.5 Ah / 4.0 Ah and approx. 55 min. for 6.0 Ah batteries. Charging time 18 V: approx 40 min for 2.5 Ah and approx 45 min for 5.0 Ah. A special procedure charges 80% of the capacity after about 30 min. With integrated battery pack cooler and overheating, discharge, and overload protection.



Accessories

Order number 466.859



Technical attributes	
Dimensions in mm	150
QTY/PKG	3

Design PH size 2, E 6,3. Can be used with screw magazine attachment M-DW 55 (463.698).


Bit holder Order number 395.919



Magnetic, design PH size 2, E 6,3. Can be used with DW 45 18.0-EC.

Technical attributes Dimensions in mm 50 QTY/PKG 1

Case insert



Matching insert for DW 45 18.0-EC for carry case L-B0XX $\!^{\!8}$ 136.

Order number 466.840

Technical attributes	
QTY/PKG	1



Accessories

Carrying case L-BOXX®



Order number 414.085

Technical attributes	
External dimensions L x W x H	442 x 357 x 151 mm
Internal dimensions L x W x H	378 x 311 x 107 mm
Weight	2,2 kg
QTY/PKG	1

The robust storage and transport system L-BOXX® made of impact-resistant plastic conveys tools, accessories and consumables easily and comfortably to the place of use. Elaborate inserts provide order and clarity, ergonomically shaped handles and additional moulded recesses for flexible and comfortable handling. The unbeatably simple connection and disconnection of the different L-BOXXes optimises combined transportation. Fits the TÜV-tested in-vehicle equipment system from Sortimo perfectly and without adapters. Load capacity per L-BOXX® up to 25 kg, combined transportation up to 40 kg, the cover can be loaded up to 100 kg. Splash-proof. Without insert, with additional front handle.

Battery powered heating jacket



Technical attributes		
Size	QTY/PKG	Order number
М	1	417.998
L	1	423.165
XL	1	423.173
XXL	1	423.181

Heated, high-quality soft shell jacket with comfortable fleece lining, various pockets, and detachable hood. Wind and water repellent material for high durability. Three heating zones for individual heating settings and quick heat function. 10,5/21 hours of heat at level 1, 9,5/19 hours at level 2, and 5/10 hours at level 3 (2,5/5,0 Ah 18,0 V). Suitable for 10,8 and 18,0 V lithium ion battery. Battery adapter with USB port for charging smartphones. Battery not included.



Accessories

LED worklamp



Order number 417.955

Technical attributes	
QTY/PKG	1

Powerful LED worklamp with 24 cold-white LEDs and integrated discharge protection. LED head can be swivelled through 320° and folded through 180°. Swivelling and lowerable hook for attaching the lamp and belt clip. Lighting duration: approx 20 hours with 2.5 Ah battery pack and approx 40 hours with 5.0 Ah battery pack. FLEX battery system: suitable for all 18 V battery packs. Delivery does not include battery.

Power 55 R



Order number 491.349

Technical attributes		
QTY/PKG	1	

Set consisting of a 10.8/18.0 V rapid charger and two 5.0 Ah 18.0 V battery packs.



Accessories

Power 22 Q



Set consisting of a 18.0 V charger and two 2.5 Ah 18.0 V battery packs.

Order number 491.357

Technical attributes	
QTY/PKG	1

Bit



Design PH size 2, C 6,3.

Order number 395.927

Technical attributes	
Dimensions in mm	25
QTY/PKG	5