

Cordless drywall screwdriver 18,0 V

DW 45 18.0-EC C



Cordless drywall screwdriver 18,0 V

+ Electronic management system (EMS) protects the machine, extends the service life, and increases efficiency

- + Brushless motor with greater efficiency and a longer service life
- + Accelerator trigger with lock-off switch
- + Electronic quick-acting brake
- + Right/left rotation with safety catch
- + Ergonomically designed, non-slip, soft grip handle
- + Integrated LED lamp with persistence function
- + LED battery capacity display
- + Ergonomically shaped soft handle with on/off switch and lock for continuous operation
- + Tool-free detachable depth stop
- + Including belt clip and bit storage

+ FLEX battery system: suitable for all 18,0 V battery packs. Delivery does not include battery and charger

Order number 491.276

Technical attributes		
18 V		
2,5 / 5,0 Ah		
28 Nm		
0-4500 rpm		
1/4" hexagon socket		
4,2 mm		
0,975 kg		

Standard equipment

1 bit holder UH-M 50 E6,3-C6,3	395.919
1 depth stop	1 piece
1 bit storage	430.862
1 belt clip	467.154



Accessories

Screw magazine attachment



Order number 463.698

0,5 kg	
1	
	0,5 kg 1

For standard, belted screws. Screw magazine attachment rotates 360°, making it easy to reach into corners, tool-free screwing depth setting via wheel, tool-free adjustable depth stop to adapt to different screw lengths from 25-55 mm, max. shank diameter 4.2 mm. Ergonomic SoftGrip handles. Fits drywall screwdriver DW 45 18.0-EC.

Li-Ion rechargeable battery pack 18,0 V



Order number 445.886

Technical attributes	
Battery capacity	2,5 Ah
Battery voltage	18,0 V
Weight	0,42 kg
QTY/PKG	1

Battery pack Li ion 18.0 V with integrated charge and discharge protection, battery charge indicator, dust and splash protection. Electronic management system (EMS) protects the battery pack, extends the service life, and increases efficiency.



Accessories

Li-Ion rechargeable battery pack 18,0 V



Order number 445.894

Technical attributes	
Battery capacity	5,0 Ah
Battery voltage	18,0 V
Weight	0,72 kg
QTY/PKG	1

Battery pack Li ion 18.0 V with integrated charge and discharge protection, battery charge indicator, dust and splash protection. Electronic management system (EMS) protects the battery pack, extends the service life, and increases efficiency.

Rapid charger



Order number 417.882 Technical attributes

1

QTY/PKG


For charging 10.8 and 18.0 V battery packs. With large-format LCD display for battery diagnostics and charge levels. Charging time 10.8 V approx. 40 min. for 2.5 Ah / 4.0 Ah and approx. 55 min. for 6.0 Ah batteries. Charging time 18 V: approx 40 min for 2.5 Ah and approx 45 min for 5.0 Ah. A special procedure charges 80% of the capacity after about 30 min. With integrated battery pack cooler and overheating, discharge, and overload protection.



Order number 466.859

Accessories

Bit



Technical attributes	
Dimensions in mm	150
QTY/PKG	3

Design PH size 2, E 6,3. Can be used with screw magazine attachment M-DW 55 (463.698).

Bit holder

Order number 395.919

50

1




QТY/РКG

Technical attributes Dimensions in mm

Magnetic, design PH size 2, E 6,3. Can be used with DW 45 18.0-EC.

Case insert



Matching insert for DW 45 18.0-EC for carry case L-BOXX[®] 136.

Order number 466.840

Technical attributes		
QTY/PKG	1	

Accessories

Carrying case L-BOXX®



Order number 414.085

Technical attributes	
External dimensions L x W x H	442 x 357 x 151 mm
Internal dimensions L x W x H	378 x 311 x 107 mm
Weight	2,2 kg
QTY/PKG	1

The robust storage and transport system L-BOXX[®] made of impact-resistant plastic conveys tools, accessories and consumables easily and comfortably to the place of use. Elaborate inserts provide order and clarity, ergonomically shaped handles and additional moulded recesses for flexible and comfortable handling. The unbeatably simple connection and disconnection of the different L-BOXXes optimises combined transportation. Fits the TÜV-tested in-vehicle equipment system from Sortimo perfectly and without adapters. Load capacity per L-BOXX[®] up to 25 kg, combined transportation up to 40 kg, the cover can be loaded up to 100 kg. Splash-proof. Without insert, with additional front handle.

Battery powered heating jacket



Technical attributes		
Size	QTY/PKG	Order number
М	1	417.998
L	1	423.165
XL	1	423.173
XXL	1	423.181

Heated, high-quality soft shell jacket with comfortable fleece lining, various pockets, and detachable hood. Wind and water repellent material for high durability. Three heating zones for individual heating settings and quick heat function. 10,5/21 hours of heat at level 1, 9,5/19 hours at level 2, and 5/10 hours at level 3 (2,5/5,0 Ah 18,0 V). Suitable for 10,8 and 18,0 V lithium ion battery. Battery adapter with USB port for charging smartphones. Battery not included.



Accessories

LED worklamp

Order number 417.955

1



Powerful LED worklamp with 24 cold-white LEDs and integrated discharge protection. LED head can be swivelled through 320° and folded through 180°. Swivelling and lowerable hook for attaching the lamp and belt clip. Lighting duration: approx 20 hours with 2.5 Ah battery pack and approx 40 hours with 5.0 Ah battery pack. FLEX battery system: suitable for all 18 V battery packs. Delivery does not include battery.

Technical attributes

QTY/PKG

Carrying bag



Order number 491.365

Technical attributes	
Size (W x L x H)	510 x 165 x 280 mm
QTY/PKG	1

Practical carrying bag made from plastic-reinforced, tear-resistant textile material with a very wide opening. With large storage space for up to three tools as well as compartments for accessories such as batteries, charger etc. and five exterior pockets on the front. Fitted with rubber feet, lockable zip fastener, cushioned carrying strap and steel-reinforced handles.



Accessories

Power 55 R



1

18Vitinii rux	
---------------	--

Set consisting of a 10.8/18.0 V rapid charger and two 5.0 Ah 18.0 V battery packs.

Power 22 Q



Set consisting of a 18.0 V charger and two 2.5 Ah 18.0 V battery packs.

Order number 491.357

Technical attributes		
QTY/PKG	1	

Technical attributes

QTY/PKG

Order number 395.927

	Ph2 Maile in
the second second	A DE RIMANI

Technical attributes		
Dimensions in mm	25	
QTY/PKG	5	

Design PH size 2, C 6,3.

Bit



