

2-speed cordless percussion drill 10,8 V

PD 2G 10.8-EC/6.0 Set

Order number 462.772



2-speed cordless percussion drill 10,8 V

- + Electronic management system (EMS) protects the machine, extends the service life, and increases efficiency
- + Brushless motor with greater efficiency and a longer service life
- + Accelerator trigger with lock-off switch
- + Electronic quick-acting brake
- + Quick-clamp chuck with auto lock function
- + Robust gearbox housing made of die-cast aluminium
- + Right/left rotation with safety catch
- + Ergonomically designed, non-slip, soft grip handle
- + Integrated LED lamp with persistence function
- + LED battery capacity display
- + Including belt clip and bit holder
- + FLEX battery system: suitable for all 10,8 V battery packs

Technical attributes

Battery voltage	10,8 V
Battery capacity	2,5 / 4,0 / 6,0 Ah
Max soft/hard torque	32 / 58 Nm
Torque positions	24+1
No load speed 1st gear	0-450 rpm
No load speed 2nd gear	0-1700 rpm
Idle blows 1st gear	0-5850 bpm
Idle blows 2nd gear	0-22100 bpm
Chuck Ø	1,5 - 13 mm
Max. drill hole Ø in steel	13 mm
Max. drill hole Ø in wood	25 mm
Max. drill hole Ø masonry	13 mm
Weight without battery	1,14 kg

Standard equipment

1 bit holder	442.380
1 belt clip	430.714
1 bit storage	430.862
2 batteries 6.0 Ah AP 10.8/6.0	438.294
1 charger CA 10.8	418.021
1 carrying case L-BOXX® 136	414.085
1 case insert	440.841

Accessories

Rapid charger 10.8 Volt

Order number 418.021



Technical attributes

QTY/PKG

1

For charging 10.8 V battery packs. With LED charging level indicator, suspension hole, high energy transfer rate and low energy consumption. Charging time approx. 40 min. for 2.5 Ah, approx. 55 min. for 4.0 Ah and approx. 85 min. for 6.0 Ah batteries.

Rapid charger

Order number 417.882



Technical attributes

QTY/PKG

1

For charging 10.8 and 18.0 V battery packs. With large-format LCD display for battery diagnostics and charge levels. Charging time 10,8 V approx. 40 min. for 2.5 Ah / 4.0 Ah and approx. 55 min. for 6.0 Ah batteries. Charging time 18 V: approx 40 min for 2.5 Ah and approx 45 min for 5.0 Ah. A special procedure charges 80% of the capacity after about 30 min. With integrated battery pack cooler and overheating, discharge, and overload protection.

FLEX-Elektrowerkzeuge GmbH
Bahnhofstraße 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX
Das Original

Accessories

Li-Ion rechargeable battery pack 10,8 V

Order number 418.048



Technical attributes	
Battery capacity	2,5 Ah
Battery voltage	10,8 V
Weight	0,26 kg
QTY/PKG	1

Battery pack Li ion 10.8 V with integrated charge and discharge protection, battery charge indicator, dust and splash protection. Electronic management system (EMS) protects the battery pack, extends the service life, and increases efficiency.

Li-Ion rechargeable battery pack 10,8 V

Order number 439.657



Technical attributes	
Battery capacity	4,0 Ah
Battery voltage	10,8 V
Weight	0,42 kg
QTY/PKG	1

Battery pack Li ion 10.8 V with integrated charge and discharge protection, battery charge indicator, dust and splash protection. Electronic management system (EMS) protects the battery pack, extends the service life, and increases efficiency.

FLEX-Elektrowerkzeuge GmbH
Bahnhofstraße 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX
Das Original

Accessories

Li-Ion rechargeable battery pack 10,8 V

Order number 438.294



Technical attributes	
Battery capacity	6,0 Ah
Battery voltage	10,8 V
Weight	0,43 kg
QTY/PKG	1

Battery pack Li ion 10.8 V with integrated charge and discharge protection, battery charge indicator, dust and splash protection. Electronic management system (EMS) protects the battery pack, extends the service life, and increases efficiency.

Angle attachment

Order number 442.372



Technical attributes	
QTY/PKG	1

Tool-free quick-change system when drilling and screwdriving in areas which are difficult to access. With magnetic drill spindle for holding drill and screwdriver bits and for holding the keyless chuck and bit holder (only for DD/PD 10.8-EC).

Accessories

Keyless chuck

Order number 442.364




With rotation stop, for clamping shank tools \varnothing 1,5-13 mm.

Technical attributes

QTY/PKG	1
---------	---

Bit holder

Order number 442.380



For holding 1/4" bits.

Technical attributes

QTY/PKG	1
---------	---

Carrying case L-BOXX®

Order number 414.085



Technical attributes

External dimensions L x W x H	442 x 357 x 151 mm
Internal dimensions L x W x H	378 x 311 x 107 mm
Weight	2,2 kg
QTY/PKG	1

The robust storage and transport system L-BOXX® made of impact-resistant plastic conveys tools, accessories and consumables easily and


FLEX-Elektrowerkzeuge GmbH
Bahnhofstraße 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX
Das Original

comfortably to the place of use. Elaborate inserts provide order and clarity, ergonomically shaped handles and additional moulded recesses for flexible and comfortable handling. The unbeatably simple connection and disconnection of the different L-BOXXes optimises combined transportation. Fits the TÜV-tested in-vehicle equipment system from Sortimo perfectly and without adapters. Load capacity per L-BOXX® up to 25 kg, combined transportation up to 40 kg, the cover can be loaded up to 100 kg. Splash-proof. Without insert, with additional front handle.

Case insert

Order number 440.841



Matching insert for DD/PD 10.8 for carry case L-BOXX® 136.

Technical attributes

QTY/PKG	1
---------	---

Bit set

Order number 455.881



Set consisting of 18 high-performance torsion bits: 2x T10, 2x T15, 2x T20, 2x T25, 2x T30, 2x T40, PH1, PH2, PH3, PZ1, PZ2, PZ3 and quick-lock bit holder.

Technical attributes

QTY/PKG	1
---------	---

Accessories

Spiral paddle RR2



Two negatively arranged spirals force the material down, preventing the liquid material from splashing. Ideal for mixing liquid to tough material: Paint, emulsions, varnishes, glazes, coatings, paste, bitumen.

Technical attributes

Paddle in mm	Mix in kg	QTY/PKG	Order number
85 Ø	- 10	1	368.946
100 Ø	8-25	1	368.954

Helix paddle WR2

Order number 368.962



Two clockwise helices for kneading and mixing tough to pasty materials. The mixer paddle screws itself down forcing the material upwards. Extremely versatile, can be used for: tile adhesive, grout, filler, finished plaster, adhesive mortar, filler compound, floor screed.

Technical attributes

Paddle in mm	85 Ø
Mix in kg	-10
QTY/PKG	1

FLEX-Elektrowerkzeuge GmbH
Bahnhofstraße 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX
Das Original

Accessories

Battery powered heating jacket



Heated, high-quality soft shell jacket with comfortable fleece lining, various pockets, and detachable hood. Wind and water repellent material for high durability. Three heating zones for individual heating settings and quick heat function. 10,5/21 hours of heat at level 1, 9,5/19 hours at level 2, and 5/10 hours at level 3 (2,5/5,0 Ah 18,0 V). Suitable for 10,8 and 18,0 V lithium ion battery. Battery adapter with USB port for charging smartphones. Battery not included.

Technical attributes

Size	QTY/PKG	Order number
M	1	417.998
L	1	423.165
XL	1	423.173
XXL	1	423.181

Helix paddle WR2



Two clockwise helices for kneading and mixing tough to pasty materials. The mixer paddle screws itself down forcing the material upwards. Extremely versatile, can be used for: tile adhesive, grout, filler, finished plaster, adhesive mortar, filler compound, floor screed.

Technical attributes

Paddle in mm	Mix in kg	QTY/PKG	Order number
100 Ø	8-20	1	368.970
120 Ø	15-25	1	368.989

Accessories

Disc paddle SR2



Technical attributes

Paddle in mm	Mix in kg	QTY/PKG	Order number
80 Ø	-10	1	369.098
100 Ø	8-15	1	369.101

Two discs with counter-running angled blades create a dynamic flow in the mixing container. The blades on the discs force the material being mixed in opposing directions downwards or upwards. Ideal for mixing liquid to tough material: Paint, emulsion, paste, glue, jointing mortar.

Beater RB



Order number 369.144

Technical attributes

Paddle in mm	120 Ø
Mix in kg	-15
QTY/PKG	1

Round mixing arms prevent air bubbles from being mixed in. Ideal for all materials where air pockets are to be avoided: filler compounds, fillers, adhesives, sealants.

FLEX-Elektrowerkzeuge GmbH
Bahnhofstraße 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX
Das Original

Accessories

Power 55 R

Order number 491.349



Set consisting of a 10.8/18.0 V rapid charger and two 5.0 Ah 18.0 V battery packs.

Technical attributes

QTY/PKG

1