

2-speed cordless percussion drill 18,0 V

PD 2G 18.0-EC C



2-speed cordless percussion drill 18,0 V

+ Electronic management system (EMS) protects the machine, extends the service life, and increases efficiency

- + Brushless motor with greater efficiency and a longer service life
- + Accelerator trigger with lock-off switch
- + Electronic quick-acting brake
- + Robust gearbox housing made of die-cast aluminium
- + Metal quick-clamp chuck with thrust ring and auto lock function
- + Right/left rotation with safety catch
- + Ergonomically designed, non-slip, soft grip handle
- + Integrated LED lamp with persistence function
- + LED battery capacity display
- + Including attachable auxiliary handle, belt clip and bit storage

+ FLEX battery system: suitable for all 18,0 V battery packs. Delivery does not include battery and charger

Order number 491.233

Technical attributes	
Battery voltage	18 V
Battery capacity	2,5 / 5,0 Ah
Max soft/hard torque	56 / 90 Nm
Torque positions	24+1
No load speed 1st gear	0-600 rpm
No load speed 2nd gear	0-2300 rpm
Blows per minute	9600-37000 bpm
Chuck Ø	1,5 - 13 mm
Max. drill hole Ø in steel	13 mm
Max. drill hole Ø masonry	16 mm
Max. drill hole Ø in wood	60 mm
Weight without battery	1,6 kg

Standard equipment

1 handle	428.698
1 belt clip	430.714
1 bit holder	453.994
1 bit storage	430.862

FLEX Das Original

Accessories

Auxiliary handle



Order number 428.698

Technical attributes		
QTY/PKG	1	

Suitable for cordless drill driver and impact drill 18,0 V.

Rapid charger




Order number 417.882

Technical attributes		
QTY/PKG	1	

For charging 10.8 and 18.0 V battery packs. With large-format LCD display for battery diagnostics and charge levels. Charging time 10,8 V approx. 40 min. for 2.5 Ah / 4.0 Ah and approx. 55 min. for 6.0 Ah batteries. Charging time 18 V: approx 40 min for 2.5 Ah and approx 45 min for 5.0 Ah. A special procedure charges 80% of the capacity after about 30 min. With integrated battery pack cooler and overheating, discharge, and overload protection.

Accessories

Case insert



Matching insert for DD/PD/ID/IW 18.0 for carry case L-BOXX[®] 136.

Carrying case L-BOXX®

FLEX Das Original

Technical attributes	
QTY/PKG	Order number
1	423.238
1	454.125

Order number 414.085

442 x 357 x 151 mm
378 x 311 x 107 mm
2,2 kg
1

The robust storage and transport system L-BOXX[®] made of impact-resistant plastic conveys tools, accessories and consumables easily and comfortably to the place of use. Elaborate inserts provide order and clarity, ergonomically shaped handles and additional moulded recesses for flexible and comfortable handling. The unbeatably simple connection and disconnection of the different L-BOXXes optimises combined transportation. Fits the TÜV-tested in-vehicle equipment system from Sortimo perfectly and without adapters. Load capacity per L-BOXX[®] up to 25 kg, combined transportation up to 40 kg, the cover can be loaded up to 100 kg. Splash-proof. Without insert, with additional front handle.



Accessories

Diamond dry drill bits



Order number 386.286

Technical attributes	
D in mm	6 Ø
T in mm	30
Linmm	80
QTY/PKG	1

For drilling without water using cordless drill drivers or drills. Drill bit with hexagonal shank for clamping in the chuck. The multi-diamond coating ensures a long service life. The core of the drill bits is filled with a solidified coolant which is melted by the heat generated during processing, thereby producing a cooling effect. For drilling dowel holes in fine stoneware (up to hardness 5), granite, marble.

Diamond dry drill bits



Order number 386.294

Technical attributes	
D in mm	8 Ø
T in mm	30
Linmm	80
QTY/PKG	1

For drilling without water using cordless drill drivers or drills. Drill bit with hexagonal shank for clamping in the chuck. The multi-diamond coating ensures a long service life. The core of the drill bits is filled with a solidified coolant which is melted by the heat generated during processing, thereby producing a cooling effect. For drilling dowel holes in fine stoneware (up to hardness 5), granite, marble.

FLEX Das Original

Accessories

Diamond dry drill bits



Order number 386.308

Technical attributes	
D in mm	10 Ø
Tinmm	30
Linmm	80
QTY/PKG	1

For drilling without water using cordless drill drivers or drills. Drill bit with hexagonal shank for clamping in the chuck. The multi-diamond coating ensures a long service life. The core of the drill bits is filled with a solidified coolant which is melted by the heat generated during processing, thereby producing a cooling effect. For drilling dowel holes in fine stoneware (up to hardness 5), granite, marble.

Diamond dry drill bits



Order number 386.316

Technical attributes	
D in mm	14 Ø
Tinmm	30
Linmm	80
QTY/PKG	1

For drilling without water using cordless drill drivers or drills. Drill bit with hexagonal shank for clamping in the chuck. The multi-diamond coating ensures a long service life. The core of the drill bits is filled with a solidified coolant which is melted by the heat generated during processing, thereby producing a cooling effect. For drilling dowel holes in fine stoneware (up to hardness 5), granite, marble.

Accessories

Tile drill bits



Technical attributes	
D in mm	5 Ø
Tinmm	50
Linmm	110
QTY/PKG	1

For drilling without water using cordless drill drivers or drills. The extremely hard tip of the drill bit is pressed gently onto the surface of the tile. This makes a precision mark for the required drill hole. As the drill bit is self-centring, it cannot slip on hard surfaces. Ideally suited for drilling dowel holes in tiles and fine stoneware up to hardness 3.

Tile drill bits



Order number 386.332

Technical attributes	
D in mm	6 Ø
Tinmm	50
Linmm	110
QTY/PKG	1

For drilling without water using cordless drill drivers or drills. The extremely hard tip of the drill bit is pressed gently onto the surface of the tile. This makes a precision mark for the required drill hole. As the drill bit is self-centring, it cannot slip on hard surfaces. Ideally suited for drilling dowel holes in tiles and fine stoneware up to hardness 3.

Tile drill bits



Order number 386.340

Technical attributes	
D in mm	8 Ø
Tinmm	50
Linmm	110
QTY/PKG	1

For drilling without water using cordless drill drivers or drills. The extremely hard tip of the drill bit is pressed gently onto the surface of the tile. This makes a precision mark for the required drill hole. As the drill bit is self-centring, it cannot slip on hard surfaces. Ideally suited for drilling dowel holes in tiles and fine stoneware up to hardness 3.

Das Original

Order number 386.324



Accessories

Li-Ion rechargeable battery pack 18,0 V



Order number 445.886

Technical attributes	
Battery capacity	2,5 Ah
Battery voltage	18,0 V
Weight	0,42 kg
QTY/PKG	1

Battery pack Li ion 18.0 V with integrated charge and discharge protection, battery charge indicator, dust and splash protection. Electronic management system (EMS) protects the battery pack, extends the service life, and increases efficiency.

Li-Ion rechargeable battery pack 18,0 V



Order number 445.894

Technical attributes		
Battery capacity	5,0 Ah	
Battery voltage	18,0 V	
Weight	0,72 kg	
QTY/PKG	1	

Battery pack Li ion 18.0 V with integrated charge and discharge protection, battery charge indicator, dust and splash protection. Electronic management system (EMS) protects the battery pack, extends the service life, and increases efficiency.

Accessories

Angle attachment

Order number 454.001

|--|--|

Technical attributesQTY/PKG1

Tool-free quick-change system when drilling and screwdriving in areas which are difficult to access. With magnetic drill spindle for holding drill and screwdriver bits and for holding the keyless chuck and bit holder (only for DD/PD 18.0-EC).

Bit holder

For holding ¼" bits.

Order number 453.994

 Technical attributes

 QTY/PKG
 1



Accessories

Keyless chuck



With rotation stop, for clamping shank tools Ø 1,5-13 mm.

Bit set

Set consisting of 18 high-performance torsion bits: 2x T10, 2x T15, 2x T20, 2x T25, 2x T30, 2x T40, PH1, PH2, PH3, PZ1, PZ2, PZ3 and quick-lock bit holder.

Order number 455.881

Technical attributes		
QTY/PKG	1	

Order number 453.986

Technical attributes		
QTY/PKG	1	







Accessories

Spiral paddle RR2



Technical attr	ibutes		
Paddle in mm	Mix in kg	QTY/PKG	Order number
85 Ø	- 10	1	368.946
100 Ø	8-25	1	368.954

Two negatively arranged spirals force the material down, preventing the liquid material from splashing. Ideal for mixing liquid to tough material: Paint, emulsions, varnishes, glazes, coatings, paste, bitumen.

Helix paddle WR2



Order number 368.962

Technical attributes	
Paddle in mm	85 Ø
Mix in kg	-10
QTY/PKG	1

Two clockwise helices for kneading and mixing tough to pasty materials. The mixer paddle screws itself down forcing the material upwards. Extremely versatile, can be used for: tile adhesive, grout, filler, finished plaster, adhesive mortar, filler compound, floor screed.



Accessories

Helix paddle WR2



Technical attri	ibutes		
Paddle in mm	Mix in kg	QTY/PKG	Order number
100 Ø	8-20	1	368.970
120 Ø	15-25	1	368.989

Two clockwise helices for kneading and mixing tough to pasty materials. The mixer paddle screws itself down forcing the material upwards. Extremely versatile, can be used for: tile adhesive, grout, filler, finished plaster, adhesive mortar, filler compound, floor screed.

Battery powered heating jacket



Technical attributes			
QTY/PKG	Order number		
1	417.998		
1	423.165		
1	423.173		
1	423.181		
	QTY/PKG 1 1 1 1		

Heated, high-quality soft shell jacket with comfortable fleece lining, various pockets, and detachable hood. Wind and water repellent material for high durability. Three heating zones for individual heating settings and quick heat function. 10,5/21 hours of heat at level 1, 9,5/19 hours at level 2, and 5/10 hours at level 3 (2,5/5,0 Ah 18,0 V). Suitable for 10,8 and 18,0 V lithium ion battery. Battery adapter with USB port for charging smartphones. Battery not included.



Accessories

Disc paddle SR2



Technical attributes				
Paddle in mm	Mix in kg	QTY/PKG	Order number	
80 Ø	-10	1	369.098	
100 Ø	8-15	1	369.101	

Two discs with counter-running angled blades create a dynamic flow in the mixing container. The blades on the discs force the material being mixed in opposing directions downwards or upwards. Ideal for mixing liquid to tough material: Paint, emulsion, paste, glue, jointing mortar.

Beater RB



Order number 369.144

Technical attributes	
Paddle in mm	120 Ø
Mix in kg	-15
QTY/PKG	1

Round mixing arms prevent air bubbles from being mixed in. Ideal for all materials where air pockets are to be avoided: filler compounds, fillers, adhesives, sealants.

Accessories

LED worklamp

Order number 417.955

1



Powerful LED worklamp with 24 cold-white LEDs and integrated discharge protection. LED head can be swivelled through 320° and folded through 180°. Swivelling and lowerable hook for attaching the lamp and belt clip. Lighting duration: approx 20 hours with 2.5 Ah battery pack and approx 40 hours with 5.0 Ah battery pack. FLEX battery system: suitable for all 18 V battery packs. Delivery does not include battery.

Technical attributes

QTY/PKG

Carrying bag



Order number 491.365

Technical attributes	
Size (W x L x H)	510 x 165 x 280 mm
QTY/PKG	1

Practical carrying bag made from plastic-reinforced, tear-resistant textile material with a very wide opening. With large storage space for up to three tools as well as compartments for accessories such as batteries, charger etc. and five exterior pockets on the front. Fitted with rubber feet, lockable zip fastener, cushioned carrying strap and steel-reinforced handles.



Accessories

Power 55 R



Order number 491.357



Set consisting of a 10.8/18.0 V rapid charger and two 5.0 Ah 18.0 V battery packs.

Power 22 Q



Set consisting of a 18.0 V charger and two 2.5 Ah 18.0 V battery packs.

QTY/PKG 1

Technical attributes

Technical attributesQTY/PKG1

FLEX Das Original